



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## VL-TURBINE1

## Up/Down Turbine LED Wall Cylinder



The **VL-TURBINE1** is ideal for parking areas, entrances, walkways, underpasses, and any other setting that is in need of enhanced safety. Since the **VL-TURBINE1** is designed to tolerate wet locations, outdoor settings are just as suitable for application as indoor settings. Along with its many features, we have included a 5 year warranty along with your investment.

### FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Operating Temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz
- IP67, suitable for wet locations
- Dimmable driver
- Operating life: >50,000 hours

### CONSTRUCTION

- Extruded round aluminum housing with built-in heat sinks
- Powder coat bronze finish (standard)
- Clear flat glass lens (standard)
- White Reflector
- Mounting: 4" recessed outlet box

### OPTIONS

- (SP) Surge Protector
- (SF) Single Fuse
- (DF) Double Fuse

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-TURBINE1-40LED	40W	3,381	5,579	5000K	80+	50,000	120-277v	50/60Hz

### Ordering Guide Example: VL-TURBINE1-40CLED-50-MV-BZ-SP

VL-TURBINE1					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-TURBINE1	40W-40CLED	50-5000K	MV=120-277V	STANDARD: BZ- BRONZE	SP-SURGE PROTECTOR SF-SINGLE FUSE DF-DOUBLE FUSE

