



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## VL-WCTRDC3

## Up/Down Turbine LED Wall Cylinder



The VL-WCTRDC3 is ideal for parking areas, entrances, walkways, underpasses, and any other setting that is in need of enhanced safety. Since the VL-WCTRDC3 is designed to tolerate wet locations, outdoor settings are just as suitable for application as indoor settings. Along with its many features, we have included a 5 year warranty along with your investment.

### FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Operating Temperatures: -30°C ~ 60°C
- Driver: Constant current, 120~277v, 50/60Hz
- IP67, suitable for wet locations
- Dimmable driver
- Operating life: >50,000 hours

### CONSTRUCTION

- Extruded round aluminum housing with built-in heat sinks
- Powder coat available in bronze and black
- Clear flat glass lens (standard)
- White Reflector
- Mounting: 4" recessed outlet box

### OPTIONS

- (SP) Surge Protector
- (SF) Single Fuse
- (DF) Double Fuse

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-WCTRDC3-40LED	40W	3,381	5,579	4100K	80+	50,000	120-277v	50/60Hz

# Ordering Guide

Example: VL-WCTRDC3-40LED-41-MV-BZ-SP

VL-WCTRDC3					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-WCTRDC3	40W-40LED	41-4100K	MV: 120~277V	BZ- BRONZE BLK-BLACK	SP-SURGE PROTECTOR SF-SINGLE FUSE DF-DOUBLE FUSE

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670  
 Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: [www.crystallighting.us](http://www.crystallighting.us)  
 Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

# Dimensions

