



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CL-FLL380

LED Flood Light



The **CL-FLL380** is strongly built with robust die cast aluminum and a tempered glass lens. The powder coat finish on this fixture is chip and fade resistant. It is also suitable for various outdoor environments. The **CL-FLL380** is commonly ideal for: wall washing, parking areas, entrances, and walkways. The **CL-FLL380** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP66, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Die cast aluminum
- Stainless steel hardware
- Tempered glass lens
- Bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
CL-FLL380-78LED	78W	8,006	13,210	4000K	70	>50,000	120V	50/60 Hz

Ordering Guide

Example: CL-FLL380-78LED-40-SF-120V-BZ

MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
CL-FLL380	78W-78LED	40-4000K	SF-SLIP FITTER	120V	BZ-BRONZE

Dimensions

