



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## CL-WPL280

## LED Wall Pack



The **CL-WPL280** is strongly built with robust die cast aluminum. The powder coat finish on this fixture is chip and fade resistant. It is suitable for various outdoor environments such as: entrances, offices, business facilities, and the exterior wall of any particular type of building. This fixture is easy to install with it's hands free mounting. The **CL-WPL280** offers competitive pricing and includes a 5 year warranty.

### FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP65, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 5 year warranty

### CONSTRUCTION

- Die cast aluminum
- Stainless steel hardware
- Tempered glass lens
- Mounts to standard 4" square electrical junction boxes
- Ingress resistant gasket included
- Bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-WPL280-78LED	78W	7,891	13,020	4000K	70	>50,000	120V	50/60 Hz

## Ordering Guide

Example: CL-WPL280-50LED-40-JB-120V-BZ

CL-WPL280

MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
CL-WPL280	78W-78LED	40-4000K	JB-JUNCTION BOX	120V	BZ-BRONZE

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670  
 Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: [www.crystallighting.us](http://www.crystallighting.us)  
 Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

# Dimensions

