



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CL-WPL280

LED Wall Pack



The **CL-WPL280** is strongly built with robust die cast aluminum. The powder coat finish on this fixture is chip and fade resistant. It is suitable for various outdoor environments. To further emphasize, a few locations that are ideal for the **CL-WPL280** are: exterior walls, entrances, and walkways. This fixture is easy to install with its hands free mounting. The **CL-WPL280** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP65, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Die cast aluminum
- Stainless steel hardware
- Tempered glass lens
- Mounts to standard 4" square electrical junction boxes
- Ingress resistant gasket included
- Bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-WPL280-40LED	40W	4,526	7,468	4000K	70	>50,000	120V	50/60 Hz
VL-WPL280-50LED	50W	5,431	8,961	4000K	70	>50,000	120V	50/60 Hz
VL-WPL280-78LED	78W	7,891	13,020	4000K	70	>50,000	120V	50/60 Hz

Ordering Guide

Example: CL-WPL280-50LED-40-JB-120V-BZ

CL-WPL280					
MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
CL-WPL280	40W-40LED	40-4000K	JB-JUNCTION BOX	120V	BZ-BRONZE
	50W-50LED				
	78W-78LED				

Dimensions

