


| DATE | |
|-------------|--|
| PROJECT | |
| ТҮРЕ | |
| NOTE | |
| PREPARED BY | |

CLC-306SM





OPTIONS

- (OCC) Motion sensor
- (PC) Button photo cell
- (EMR) Emergency battery backup
- (QM) Hinged Quick-Mount Bracket, Stamped Steel, Mount Over Recessed Electrical Box, or Use ¾" NPS Down-rod for Pendant Mounting

18" sq. LED garage or gas station light fixture

18" sq. LED garage or gas station light fixture, suitable for wet locations, Perfect for lighting up underpasses, hallways, entry ways, storage areas, parking garages, loading docks, Industrial/commercial spaces. This fixture has a wide light distribution. Comes with a 5 year/50,000 hour limited warranty.

FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: $-30^{\circ}\text{C} \sim 60^{\circ}\text{C}$
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell capable (optional)
- Operating Life: >60,000 hours

CONSTRUCTION

- Housing is heavy-duty die-cast aluminum backing
- 1/2" Coin plugs with O-rings for conduit, sensors or photo cell
- Powder coat white finish (standard) various colors available (custom).
- Clear prismatic glass lens
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box or use ½" Surface Conduit





| Model Number | INPUT POWER | LUMEN OUTPUT | SCOPTIC | COLOR TEMP (CCT) | CRI | RATED LIFE (L70) | INPUT VOLTAGE | INPUT FREQUENCY | HID Equivalent |
|-------------------|----------------|-----------------|---------|---------------------|-----|---------------------|------------------|--------------------|-------------------|
| CLC-306SM-80CLED | 85W | 11,008 | 18,163 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 250w HPS |
| CLC-306SM-100CLED | 105W | 11,926 | 19,081 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 400w PSMH |
| CLC-306SM-120CLED | 125W | 16,512 | 26,419 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 400w HPS |

Ordering Guide Example: (CLC-306SM-80CLED-50-MV-WH-PC)

| CLC-306SM | | | | | |
|-----------|--|---|-------------------------|--|--|
| MODEL | WATTS | COLOR TEMP | VOLTAGE | FINISH | OPTIONS |
| CLC-306SM | 80W-80CLED 100W-100CLED 120W-120CLED | 27-2700K 30-3000K 35-3500K 40-4000K 50-5000K 57-5700K 65-6500K | MV=120-277V 480-480V | BZ- BRONZE GRY-GRAY BLK-BLACK WH- WHITE CUS-CUSTOM | OCC- MOTION SENSOR PC- BUTTON PHOTOCELL EMR- EMR BATTERY QM-QUICK MOUNT |

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670 Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: www.crystallighting.us
Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA