

| | |
|-------------|--|
| DATE | |
| PROJECT | |
| TYPE | |
| NOTE | |
| PREPARED BY | |

MD-CLW-3031

Full cut off LED wallpack



The **MD-CLW-3031** is a small full cut off LED wall pack fixture suitable for wet locations. It is perfect for enhancing security in various locations such as: residential exteriors, walkways, entry ways, perimeters, parking garages, school campuses, and industrial/commercial spaces. The **SM-CLW-3031** has a wide rectangular light distribution. It is also dark-sky compliant and DLC listed. Along with your investment in the **SM-CLW-3031** comes a 10 year warranty.

FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell capable (optional)

OPTIONS

- (OCC) Motion sensor
- (PC) Button photo cell
- (EMR) Emergency battery backup
- (GLE) Etched flat glass lens
- (GLP) Prismatic flat glass lens
- (LG) Clear polycarbonate vandal resistant guard
- (WG) Wire guard stainless steel

CONSTRUCTION

- Housing is heavy-duty die-cast aluminum
- 1/2" Coin plugs with O-rings for conduit, sensors or photo cell
- Powder coat **bronze finish (standard)** various colors available (custom).
- Clear tempered glass lens
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box



| Model Number | INPUT POWER | LUMEN OUTPUT | SCOP-TIC | COLOR TEMP (CCT) | CRI | RATED LIFE (L70) | INPUT VOLTAGE | INPUT FREQUENCY | HID Equivalent | DLC LISTED |
|---------------------|-------------|--------------|----------|------------------|-----|------------------|---------------|-----------------|----------------|------------|
| MD-CLW-3031-20CLED | 25W | 2,750 | 4,530 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 100w MH | PENDING |
| MD-CLW-3031-60CLED | 65W | 8,256 | 13,622 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 250w PSMH | NO |
| MD-CLW-3031-80CLED | 85W | 11,008 | 18,163 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 250w HPS | NO |
| MD-CLW-3031-100CLED | 105W | 13,760 | 22,704 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 400w PSMH | PENDING |
| MD-CLW-3031-120CLED | 125W | 16,512 | 26,419 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 400w HPS | PENDING |

Ordering Guide

Ordering Guide

Example: (MD-CLW-3031-60CLED-50-MV-BZ-PC)

| MD-CLW-3031 | | | | | | |
|-------------|---|---|------------------------------------|---|---|---|
| MODEL | WATTS | COLOR TEMP | VOLTAGE | FINISH | OPTIONS | DISTRIBUTION |
| MD-CLW-3031 | 20W-20CLED 60W-60CLED 80W-80CLED 100W-100CLED 120W-120CLED | 27-2700K 30-3000K 35-3500K 40-4000K 50-5000K 57-5700K 65-6500K | MV=120-277V 480-480V | <u>STANDARD</u> BZ- BRONZE <u>ADD'L CHARGE</u> BLK-BLACK GRY-GRAY WH- WHITE CUS-CUSTOM | EMR- EMR BATTERY FCV- FULL CUTOFF VISOR GS- GLARE SHIELD LG- POLYCARB COVER OCC- MOTION SENSOR PC- BUTTON PHOTOCELL SCS-SIDE CUTOFF SHIELD WC- WIRELESS CONTROL WG- WIRE GUARD | T1-TYPE 1 T2-TYPE 2 T3-TYPE 3 T4-TYPE 4 T5-TYPE 5 |

Dimensions

