

DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## MD-CLW-3031

## Full cut off LED wallpack

The **MD-CLW-3031** is a small full cut off LED wall pack fixture suitable for wet locations. It is perfect for enhancing security in various locations such as: residential exteriors, walkways, entry ways, perimeters, parking garages, school campuses, and industrial/commercial spaces. The **SM-CLW-3031** has a wide rectangular light distribution. It is also dark-sky compliant and DLC listed. Along with your investment in the **SM-CLW-3031** comes a 10 year warranty.



### FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell capable (optional)

### OPTIONS

- (OCC) Motion sensor
- (PC) Button photo cell
- (EMR) Emergency battery backup
- (GLE) Etched flat glass lens
- (GLP) Prismatic flat glass lens
- (LG) Clear polycarbonate vandal resistant guard
- (WG) Wire guard stainless steel

### CONSTRUCTION

- Housing is heavy-duty die-cast aluminum
- 1/2" Coin plugs with O-rings for conduit, sensors or photo cell
- Powder coat **bronze finish (standard)** various colors available (custom).
- Clear tempered glass lens
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box



Model Number	INPUT POWER	LUMEN OUTPUT	SCOP-TIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent	DLC LISTED
MD-CLW-3031-20CLED	25W	2,750	4,530	5000K	70+	>200,000	120-277V	50/60HZ	100w MH	PENDING
MD-CLW-3031-54LED	56W	3,933	6,292	5000K	70+	>200,000	120-277V	50/60HZ	250w PSMH	YES
MD-CLW-3031-60CLED	65W	8,256	13,622	5000K	70+	>200,000	120-277V	50/60HZ	250w PSMH	NO
MD-CLW-3031-80CLED	85W	11,008	18,163	5000K	70+	>200,000	120-277V	50/60HZ	250w HPS	NO
MD-CLW-3031-100CLED	105W	13,760	22,704	5000K	70+	>200,000	120-277V	50/60HZ	400w PSMH	PENDING
MD-CLW-3031-120CLED	125W	16,512	26,419	5000K	70+	>200,000	120-277V	50/60HZ	400w HPS	PENDING

# Ordering Guide

**Ordering Guide**

Example: (MD-CLW-3031-60CLED-50-MV-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
MD-CLW-3031	20W-20CLED <b>60W-60CLED</b> 80W-80CLED 100W-100CLED 120W-120CLED	27-2700K 30-3000K 35-3500K 40-4000K <b>50-5000K</b> 57-5700K 65-6500K	<b>MV=120-277V</b>  480-480V	<u>STANDARD</u> <b>BZ- BRONZE</b>  <u>ADD'L CHARGE</u> GRY-GRAY BLK-BLACK WH- WHITE CUS-CUSTOM	OCC- MOTION SENSOR <b>PC- BUTTON PHOTOCCELL</b> EMR- EMR BATTERY LG- POLYCARB COVER WG- WIRE GUARD FCV- FULL CUTOFF VISOR GS- GLARE SHIELD SCS-SIDE CUTOFF SHIELD WC- WIRELESS CONTROL

# Dimensions

