

DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

SM-CLW-3031

Full cut off LED wallpack

The **SM-CLW-3031** is a small full cut off LED wall pack fixture suitable for wet locations. It is perfect for enhancing security in various locations such as: residential exteriors, walkways, entry ways, perimeters, parking garages, school campuses, and industrial/commercial spaces. The **SM-CLW-3031** has a wide rectangular light distribution. It is also dark-sky compliant and DLC listed. Along with your investment in a **SM-CLW-3031** comes a 10 year warranty.



FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell capable (optional)
- Operating Life: >60,000 hours

CONSTRUCTION

- Housing is heavy-duty die-cast aluminum
- 1/2" Coin plugs with O-rings for conduit, sensors or photo cell
- Powder coat **bronze finish (standard)** various colors available (custom).
- Clear tempered glass lens
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box or use 1/2" Surface Conduit

OPTIONS

- (OCC) Motion sensor
- (PC) Button photo cell
- (EMR) Emergency battery backup
- (GLE) Etched flat glass lens
- (GLP) Prismatic flat glass lens
- (LG) Clear polycarbonate vandal resistant guard
- (WG) Wire guard stainless steel

Model Number	INPUT POWER	LUMEN OUTPUT	SCOP-TIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent	DLC LISTED
SM-CLW-3031-5CLED	7W	757	1,211	5000K	70+	>200,000	120-277V	50/60HZ	35w HPS	NO
SM-CLW-3031-10CLED	12W	1,376	2,201	5000K	70+	>200,000	120-277V	50/60HZ	50w HPS	NO
SM-CLW-3031-15CLED	20W	1,918	3,068	5000K	70+	>200,000	120-277V	50/60HZ	70w HPS	NO
SM-CLW-3031-21CLED	25W	3,102	4,963	5000K	70+	>200,000	120-277V	50/60HZ	100w HPS	NO
SM-CLW-3031-36LED	34W	2,468	3,948	5000K	70+	>200,000	120-277V	50/60HZ	100w HPS	YES
SM-CLW-3031-40CLED	45W	5,504	8,806	5000K	70+	>200,000	120-277V	50/60HZ	150w HPS	NO
SM-CLW-3031C-40LED	39W	2,857	4,569	5000K	70+	>200,000	120-277V	50/60HZ	100w MH	YES
SM-CLW-3031C-76LED	76W	5,449	8,718	5000K	70+	>200,000	120-277V	50/60HZ	150w HPS	YES

Ordering Guide

Ordering Guide Example: (SM-CLW-3031-40CLED-50-MV-BZ-PC)

SM-CLW-3031					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
SM-CLW-3031	5W-5CLED 10W-10CLED 15W-15CLED 21W-21CLED 36W-36LED 40W-40CLED 40W-40LED 76W-76LED	27-2700K 30-3000K 35-3500K 40-4000K 50-5000K 57-5700K 65-6500K	MV=120-277V 480-480V	<u>STANDARD FINISH</u> BZ- BRONZE <u>ADD'L CHARGE:</u> GRY-GRAY BLK-BLACK WH- WHITE CUS-CUSTOM	OCC- MOTION SENSOR PC- BUTTON PHOTOCELL EMR- EMR BATTERY GLE- ETCHED FLAT GLASS GLP- PRISMATIC FLAT GLASS LG- POLYCARB COVER WG- WIRE GUARD WC- WIRELESS CONTROL

Dimensions

