



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## VL-1000

## LED Flood/Area Light



The **VL-1000** is strongly built with precision die cast aluminum and with a chip/fade resistant powder coat finish. It is suitable for various outdoor environments. The **VL-1000** is commonly ideal for: wall washing, parking areas, entrances, walkways, and underpasses. The **VL-1000** offers competitive pricing and includes a 3 year warranty.

### FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP66, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty



### CONSTRUCTION

- Precision die cast
- Swivel bracket and Slip fitter mount available
- Chip and fade resistant powder coat finish
- Bronze finish (standard)

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-1000-250LED	250W	27,935	46,093	4000K	70	>50,000	120V	50/60 Hz
VL-1000-300LED	300W	34,284	56,568	4000K	70	>50,000	120V	50/60 Hz
VL-1000-400LED	400W	44,723	73,793	4000K	70	>50,000	120V	50/60 Hz

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670

Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: [www.crystallighting.us](http://www.crystallighting.us)

Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

# Ordering Guide

Example: VL-1000-80LED-40-SM-120V-BZ

MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
VL-1000	250W-250LED 300W-300LED 400W-400LED	40-4000K	SB-SWIVEL BRACKET SF-SLIP FITTER	120V	BZ-BRONZE

## Dimensions

