



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-FB1C3

LED Bullet



The first advantage of the **VL-FB1C3** is that it's a multifunctional installation; it can be mounted with a knuckle mount or a pendant mount. It is ideal for wet outdoor or indoor locations such as: residential, institutional, commercial and multifamily locations. This fixture is energy efficient, durable, and requires low maintenance. The **VL-FB1C3** fixture offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- Wet location rated
- 4100K
- IP67
- 120~277V
- 80+ CRI
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Tempered clear flat glass lens
- Die-Cast aluminum housing
- Mounting: ½" NPS Knuckle (included), or Pendant Mount with ½" conduit (not included)
- Built-in heat sinks
- Powder coat finish (bronze; standard)
- White reflector

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-FB1C3-20LED	20W	1,800	2,970	4100K	80+	>50,000	120~277V	50/60 Hz

Ordering Guide

Example: VL-FB1C3-20LED-41-MV-BZ-KN-SF

VL-FB1C3	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING	OPTIONS
VL-FB1C3	20W-20LED	41-4100K	MV-120~277V	BZ-BRONZE	KN-KNUCKLE MOUNT (included) PM-PENDANT MOUNT (not included)	SF-SINGLE FUSE DF-DOUBLE FUSE SP-SURGE PROTECTION

Dimensions

