



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-FLL360

LED Flood Light



The **VL-FLL360** is strongly built with robust die cast aluminum. The powder coat finish on this fixture is chip and fade resistant. It is suitable for various outdoor environments. To further emphasize, a few locations that are ideal for the **VL-FLL360** are: wall parking areas, entrances, walkways, underpasses, etc. The **VL-FLL360** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP65, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Die cast aluminum
- Stainless steel hardware
- Tempered glass lens
- Bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-FLL360-20LED	20W	2,181	3,598	4000K	70	>50,000	120V	50/60 Hz

Ordering Guide

Example: VL-FLL360-20LED-40-SF-120V-BZ

VL-FLL360					
MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
VL-FLL360	20W-20LED	40-4000K	SF-SLIP FITTER	120V	BZ-BRONZE

Dimensions

