



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-FLL370

LED Flood Light



The VL-FLL370 is strongly built with robust die cast aluminum. The powder coat finish on this fixture is chip and fade resistant. It is suitable for various outdoor environments. To further emphasize, a few locations that are ideal for the VL-FLL370 are: exterior walls, parking areas, walkways, and underpasses. The VL-FLL370 offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP66, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Die cast aluminum
- Stainless steel hardware
- Tempered glass lens
- Bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-FLL370-38LED	38W	4,013	6,621	4000K	70	>50,000	120V	50/60 Hz
VL-FLL370-40LED	40W	4,733	7,809	4000K	70	>50,000	120V	50/60 Hz
VL-FLL370-50LED	50W	5,584	9,214	4000K	70	>50,000	120V	50/60 Hz

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670

Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: www.crystallighting.us

Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

Ordering Guide

Example: VL-FLL370-40LED-40-SF-120V-BZ

VL-FLL370					
MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
VL-FLL370	38W-38LED 40W-40LED 50W-50LED	40-4000K	SF-SLIP FITTER	120V	BZ-BRONZE

Dimensions

