



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-FLL400

LED Flood Light



The **VL-FLL400** is strongly built with robust die cast aluminum. The powder coat finish on this fixture is also chip and fade resistant. It is suitable for various outdoor environments. To further emphasize, a few locations that are ideal for the **VL-FLL400** are: recreational parks, parking areas, and walkways. The VL-FL400 offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP66, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Precision die cast aluminum
- Stainless steel hardware
- Tempered glass lens
- Bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-FLL400-100LED	100W	11,113	18,336	4000K	70	>50,000	120V	50/60 Hz
VL-FLL400-114LED	114W	11,717	19,333	4000K	70	>50,000	120V	50/60 Hz

Ordering Guide

Example: VL-FLL400-114LED-40-SF-120V-BZ

VL-FLL400					
MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
VL-FLL400	100W-100LED 114W-114LED	40-4000K	SF-SLIP FITTER	120V	BZ-BRONZE

Dimensions

