



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-GLL450

LED Garage Light

The **VL-GLL450** is strongly built with robust die cast aluminum and a tempered glass lens. The powder coat finish on this fixture is chip and fade resistant. It is suitable for various outdoor environments. The **VL-GLL450** is commonly ideal for: ceiling mounts, residential, institutional, and multifamily locations. The surface mount on this fixture is easy to install and requires low maintenance. The **VL-GLL450** offers competitive pricing and includes a 3 year warranty.



FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP66, rated outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- Prismatic reflector
- 3 year warranty

CONSTRUCTION

- Die cast aluminum
- Stainless steel hardware
- Tempered glass lens
- Bronze finish (standard)

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-GLL450-60LED	60W	6,000	9,900	4000K	70	>50,000	120V	50/60 Hz
VL-GLL450-80LED	80W	7,706	12,715	4000K	70	>50,000	120V	50/60 Hz

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670

Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: www.crystallighting.us

Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

Ordering Guide

Example: VL-GLL450-80LED-40-SM-120V-BZ

VL-GLL450					
MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
VL-GLL450	60W-60LED 80W-80LED	40-4000K	SM-SURFACE MOUNT	120V	BZ-BRONZE

Dimensions

