



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-OVL500

LED Wall Pack



The **VL-OVL500** is strongly built with polycarbonate and an aluminum back plate. The powder coat finish on this fixture is chip and fade resistant. It is also suitable for various wet outdoor environments. The **VL-OVL500** is commonly ideal for: exterior walls, entrances, building walls, and indoor walkways . The **VL-OVL500** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- IP66, rated wet location/outdoor use
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty
- Easy installation with hands free mounting

CONSTRUCTION

- Polycarbonate with aluminum back plate
- Wall mount
- Frosted UV stabilized polycarbonate Diffuser
- Bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-OVL500-10LED	10W	1,027	1,694	4000K	70	>50,000	120V	50/60 Hz
VL-OVL500-15LED	15W	1,433	2,364	4000K	70	>50,000	120V	50/60 Hz
VL-OVL500-20LED	20W	1,746	2,881	4000K	70	>50,000	120V	50/60 Hz

Ordering Guide

Example: VL-OVL500-78LED-40-WM-120V-BZ

VL-OVL500					
MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
VL-OVL500	10W-10LED 15W-15LED 20W-20LED	40-4000K	WM-WALL MOUNT	120V	BZ-BRONZE

Dimensions

