



ASTRAL Post Mount is a combination of security, style and Vandal resistance, AST-PM blends into any pathway environment. This Luminaire ranges from 18 to 50 Watts, Types 2, 3, 4, and Type 5 light distribution. Kelvin Temperature 30K, 40K and 50K available.

Finished with 3 Mil Powder Coat and All Hardware stainless steel. ASTRAL PM is Proudly designed, fabricated and Assembled in the USA.

Warranty:


- -10 year/100,000 hour Limited Warranty.
- -Dark Sky Compliant

Features:

- Energy Savings: Over 66% compared to HID light sources.
- Improved Lumen Maintenance.
- Utilizes High efficient Lumiled LED's.
- Operating Temperatures: -30°C ~ 60°C.
- Driver: 120-277V (MV) or 480V (HV) (Optional).
- IP65 / IP67 Rated.
- 0-10 Dimming Driver, Occupancy Sensors, Photo Cell or Wireless Controls (Optional)

Construction:

- Corrosion-Resistant Cast Aluminum Housing
- 3 Mil Powder Coat Finish.
- Clear Optic, Types 2, 3, 4 and 5 IP67 Rated (Options)
- Silicone Gasket to provide Weather-Tight Protection (IP66).
- Mounting: Over of a 3" Pole or Tenon (Adapter is required for other mountings Options)



TYPE 2(T2) TYPE 3(T3) TYPE 4(T4) TYPE 5(T5)





(mg)










Example: AST-PM-20CLED-T3-40K-MV-BRZ-30D-PC

example. Hat Fill 20020D 13 40K TIV BK2 30D FC								
Cat#	Wattage	Light Dist.	Color Temp.	Voltage	Color	Mounting	Options	
АЅТ-РМ								
ASTRAL-PM (AST-PM)	20W (20CLED)	Type 2 (T2)	3000K (30K)	120-277V (mv)	Black (BLK)	Post Top 3" OD	Button Photo Cell (PC)	
	40W (40CLED) 50W (50CLED)	Type 3 (T3)	4000K (40K)		White (WH) Bronze (BRZ) Silver (SIL)	(3RD)	Wireless controls (WC)	
			5000K (50K)				House Side Shield	
							(HSS)	
					Graphite (GPH)			
					Marine Grade			







Dimensions								
Cat#	А	В	εра					
AST-PM	22"	8"	.69					

<u>DA-M156</u>



DA-7

Arm Options



CLP-X155

DA-246B





Cat #	Input Power	Lumen Output	LPW	Color Temp. (CCT)	CRI	Rated Life (L70)	Imput Voltage	HID Equivalent	HID Equivalent
AST-PM-20CLED	25W	3,175	158	5000K	70+	>200,000	120-277V	50/60HZ	100W MH
AST-PM-40CLED	45W	5,757	143	5000K	70+	>200,000	120-277V	50/60HZ	150W MH
AST-PM-50CLED	55W	6,643	132	5000K	70+	>200,000	120-277V	50/60HZ	175W MH

Proudly Manufactured and Assembled in the USA





Crystal Lighting 13182 Flores ST. Santa Fe Springs , CA. 90670 Ph: 562-944-0223 www.crystallighting.us